

Simrit UL Listed Compounds

	N470	V75	V75BR	V121	V123
UL 157, JMLU2, File MH16378	Temp. range = -54°C to 60°C	Temp. Range = -40°C to 105°C	Temp. Range = -30°C to 105°C	Temp. Range = -40°C to 105°C	Temp. Range = -40°C to 105°C
Gasoline		X	X	X	X
Naphta or Kerosene	X	X	X	X	X
MPS Gas	X				
Manufactured Gas or Natural Gas	X	X		X	X
Diesel Fuel, Fuel Oil or Lubricating Oil	X	X	X	X	X
Anhydrous Ammonia	X				
Liquified Petroleum Gas (LP-Gas)	X	X		X	X
Dry Chemical, Carbon Dioxide, Water (fire extinguishers)	X	X			
Heated Fuel Oil		X			
Gasoline/Alcohol Blends				X	X
Gasoline/ethanol and gasoline methanol blends with a concentration up to 15% ethanol or methanol				X	X
Gasoline/ethanol blends higher than 15% ethanol (static and dynamic applications)				X	X
Gasoline with a maximum of 15 percent, MTBE				X	
Suitable for 0-20 percent MTBE/Gasoline blends					X
Suitable for 0-20 percent ETBE/Gasoline blends					X
Suitable for 0-17 percent TAME/Gasoline blends					X

The information contained herein is believed to be reliable, but no representation, guarantees or warranties of any kind are made to its accuracy or suitability for any purpose. The information presented herein is based on laboratory testing and does not necessarily indicate end product performance. Full scale testing and end product performance are the responsibility of the user.

© Copyright FNGP 2009